




**SOLUTIONS FOR BATTERY VEHICLES
BRUSHLESS MOTORS**



LET'S MOVE TO THE NEXT STEP

ENTER INTO THE FUTURE

CANopen

EtherCAT

Safety over

EtherCAT





**QUALITY
SOLUTIONS
TECHNOLOGY**

BRUSHLESS MOTORS KBL57



MOTOR TYPE	<i>KBL57-19</i>	<i>KBL57-35</i>	<i>KBL57-75</i>	
NUMBER OF POLES	6			
NOMIAL DC VOLTAGE	12 – 24 – 36 – 48			<i>V</i>
RATED POWER	<i>35 - 100</i>	<i>70 - 250</i>	<i>130 - 400</i>	<i>W</i>
RATED SPEED	1500 – 3000 – 4500 - 6000			<i>rpm</i>
CONTINUOS TORQUE	<i>0,2</i>	<i>0,4</i>	<i>0,8</i>	<i>Nm</i>
PEAK TORQUE	<i>0,6</i>	<i>1,2</i>	<i>2,4</i>	<i>Nm</i>
FEEDBACK	<i>3x digital hall sensor</i>			
IP PROTECTION	43			
INSULATION CLASS	<i>class B</i>			
AXIAL LENGTH L'	<i>55</i>	<i>69</i>	<i>105</i>	<i>mm</i>





FEATURES AVAILABLES

- optional feedback sensor, incremental or absolute encoders, resolver and protocols
- mechanical available NEMA23, MEC56 B14, MEC63 B14 and custom design
- 2nd shaft end for EM brake or feedback sensor available
- cable exit with or without connectors
- upgradeable enclosure IP protection
- integrated electronic design available

BRUSHLESS MOTORS KBL86Q



MOTOR TYPE	<i>KBL86Q-90</i>	<i>KBL86Q-130</i>	
NUMBER OF POLES	8		
NOMIAL DC VOLTAGE	12 – 24 – 36 – 48 – 72 – 80 – 96 up to 400		<i>V</i>
RATED POWER	220 – 450 – 600	400 – 750 – 1000	<i>W</i>
RATED SPEED	1500 – 3000 – 4500 – 6000		<i>rpm</i>
CONTINUOUS TORQUE	1,5	2,5	<i>Nm</i>
PEAK TORQUE	4,5	7,5	<i>Nm</i>
FEEDBACK	3x digital hall sensor		
IP PROTECTION	43		
INSULATION CLASS	class B		
AXIAL LENGTH L'	90	130	<i>mm</i>





FEATURES AVAILABLES

- optional feedback sensor, incremental or absolute encoders, resolver and protocols
- mechanical available NEMA34, MEC63 B14, MEC71 B14 and custom design
- 2nd shaft end for EM brake or feedback sensor available
- cable exit with or without connectors
- upgradeable enclosure IP protection
- integrated electronic design available

BRUSHLESS MOTORS KBL100



MOTOR TYPE	<i>KBL100-30</i>	<i>KBL100-40</i>	<i>KBL100-50</i>	<i>KBL100-60</i>	
NUMBER OF POLES	8				
NOMIAL DC VOLTAGE	12 – 24 – 36 – 48 – 72 – 80 – 96				V
RATED POWER	300-600	400-1000	800-1200	800-1200	W
RATED SPEED	1500 – 3000 – 4500- 6000				rpm
CONTINUOS TORQUE	1,9	2,8	4,4	4,4	Nm
PEAK TORQUE	4	5,8	12	12	Nm
FEEDBACK	3x digital hall sensor				
IP PROTECTION	43				
INSULATION CLASS	class F				
AXIAL LENGHT <i>L'</i>	76	86	96	106	mm





FEATURES AVAILABLES

- optional feedback sensor; incremental or absolute encoders, resolver and protocols
- mechanical available MEC63 B14, MEC71 B5 or B14, MEC80 B5 or B14 and custom designs
- 2nd shaft end for EM brake or feedback sensor available
- cable exit with or without connectors
- upgradeable enclosure IP protection
- integrated electronic design available

BRUSHLESS MOTORS KBL127



MOTOR TYPE	<i>KBL127-35</i>	<i>KBL127-70</i>	<i>KBL127-100</i>	
NUMBER OF POLES	12			
NOMIAL DC VOLTAGE	12 – 24 – 36 – 48 – 72 – 80 – 96 up to 400			<i>V</i>
RATED POWER	<i>750 - 1500</i>	<i>1500 - 3000</i>	<i>3000 – 6000</i>	<i>W</i>
RATED SPEED	1500 – 3000 – 4500 - 6000			<i>rpm</i>
CONTINUOUS TORQUE	<i>3,5</i>	<i>7</i>	<i>12</i>	<i>Nm</i>
PEAK TORQUE	<i>14</i>	<i>28</i>	<i>36</i>	<i>Nm</i>
FEEDBACK	<i>3x digital hall sensor</i>			
IP PROTECTION	43			
INSULATION CLASS	<i>class F</i>			
AXIAL LENGHT L'	<i>97</i>	<i>132</i>	<i>162</i>	<i>mm</i>



FEATURES AVAILABLES

- optional feedback sensor, incremental or absolute encoders, resolver and protocols
- mechanical available MEC71 B5 or B14, MEC80 B5 or B14, MEC90 and custom designs
- 2nd shaft end for EM brake or feedback sensor available
- cable exit with or without connectors
- upgradeable enclosure IP protection
- integrated electronic design available with different BUS comunicatio

TAILOR MADE SOLUTIONS



BLDC MOTOR KBL57-19-24070

Compact solution with HIGH POWER DENSITY
Custom mechanical design for gearbox integration
WITHOUT DE bearing, for optimal couplig on gears
Certified by customer for ATEX application

nominal performances 24V 100W 10000 RPM

BLDC MOTOR KBL57-35-24135.D

mechanical design for HIGH WEAR RESISTANCE and
CUSTOM PUMP INTERFACE
integrated driver for motor regulation
POWER+SIGNAL hybrid connector
IP68 enclosure with pump mounted

nominal performances 24V 135W 3500 RPM



BLDC MOTOR KBL86Q-90-24200.D

Compact solution with HIGH POWER DENSITY
mechanical design for CUSTOM PUMP INTERFACE
integrated driver for motor regulation
POWER+SIGNAL hybrid connector
IP68 enclosure with pump mounted

nominal performances 24V 200W 2000 RPM



BLDC MOTOR KBL100-50-481K0.D

Compact solution with HIGH POWER DENSITY
Integrated motor driver, just +B and -B for start
Pump unit application for pump group 1
IP56 enclosure

nominal performances 48V 800W 1500 RPM



BLDC MOTOR KBL100-50-481K0.D

Compact solution with HIGH POWER DENSITY
Integrated motor driver, just +B and -B for start
Custom mechanical design for high radial load
Hot galvanized for high wear resistance
IP67 enclosure

nominal performances 48V 800W 1300 RPM



BLDC MOTOR KBL127-35-241K5.F

Compact solution with HIGH POWER DENSITY
IP67 enclosure

nominal performances 24V 1500W 3600 RPM





HIGH PERFORMANCE BRUSHLESS MOTORS w/ INTEGRATED DRIVE

from 12 to 300 V
from 10 W to 20 kW
from 1 to 20000 rpm

MOTOR- IN-WHEEL DRIVES and VERTICAL DRIVES READY TO GO

from 12 to 120 V
from 50 Kg to 15 tons
with or without integrated drivers



ELMO MOTION CONTROL PARTNER

motion control drives for high performance solution & amazing integrated application

www.elmomc.com

GEBRÜDER FREI OFFICIAL DEALER

control system for transport technology for any kind of applications and for any environment

www.frei.de/en/



ROBOTEQ SOLUTION PARTNER

brushless and induction low voltage motor controllers to get max performance from our motors

www.roboteq.com/

SCHABMÜLLER OFFICIAL PARTNER

AGV Italian business responsibility southern Europe SERIVE CENTRE more than 50'000 spare parts on stock

www.schabmueller.de/en/



REPAIRING THE IMPOSSIBLE

with almost 70 years experience, we are specialized in electrical motor service, traction, steering and electrical pump motors for forklifts, AGVs, tugs, walkies, electric cars and all electrical vehicles



KELVIN S.r.l.

*via Massimo d'Azeglio, 28
21010 Besnate - VA
ITALY*

phone +39 0331 274136

fax +39 0331 275550

info@kelvin.it

www.kelvin.it