

CATALOGO MOTORI



SRL

CODICE: **KLMT2829-**

64A8070



ROTAZIONE V.L.A.: Entrambi i sensi

Ø 152 X 237 mors 4

CARR.: **STEINBOCK** STEINBOCK

MOTORE: **LEROY**

TIPO: **TF15**

ARM. V1: **24** A1: **82**

ECC.: **SERIE**

V2: A2:

KW: **1,** HP

U./MIN: **2760**

APPLIC.: **Trazione**

SERV: **S2-60'**

CODICE: **KLMT1087-**

050762

00050762



ROTAZIONE V.L.A.: Entrambi i sensi

Ø 178 X 270 mors 4

CARR.: **STEINBOCK** STEINBOCK

MOTORE: **SCHABMULLER**

TIPO: **R178/3K-121/77**

ARM. V1: **23** A1: **160**

ECC.: **SERIE**

V2: A2:

KW: **3** HP

U./MIN: **1700**

APPLIC.: **Trazione**

SERV: **S2 = 60'**

CODICE: **KLMT1075-**

028640

00028640

50154574Jun

9000140068



ROTAZIONE V.L.A.: Entrambi i sensi

Ø 178 X 270 mors 4

CARR.: **STEINBOCK** STEINBOCK

MOTORE: **SCHABMULLER**

TIPO: **R178/3K-517/513**

ARM. V1: **23** A1: **165**

ECC.: **SERIE**

V2: A2:

KW: **3** HP

U./MIN: **1705**

APPLIC.: **Trazione**

SERV: **S2 - 60'**

CODICE: **KLMT3124-**



ROTAZIONE V.L.A.: Entrambi i sensi

Ø 150 X 295 mors 7

CARR.: **STEINBOCK** STEINBOCK

MOTORE: **SCHABMULLER**

TIPO: **R150/2-31/25**

ARM. V1: **24** A1: **114**

ECC.: **SERIE**

V2: A2:

KW: **2** HP

U./MIN: **1890**

APPLIC.: **Trazione**

SERV: **S2-30'**

CODICE: **KLMT1060-**

014520



ROTAZIONE V.L.A.: Entrambi i sensi

Ø 150 X 255 mors 7

CARR.: **STEINBOCK** STEINBOCK

MOTORE: **SCHABMULLER**

TIPO: **R150/1-36/27**

ARM. V1: **24** A1: **60**

ECC.: **SERIE**

V2: A2:

KW: **1** HP

U./MIN: **1400**

APPLIC.: **Trazione**

SERV:

CATALOGO MOTORI



SRL

CODICE: **KLMT1080-**

0029130

50154793



ROTAZIONE V.L.A.: Entrambi i sensi

Ø 178

X 310

mors 4

CARR.: **STEINBOCK**

WA12 - WA15

MOTORE: **SCHABMULLER**

TIPO: **R178/5K- 529/524**

ARM. V1: **76**

A1: **82**

ECC.: **SERIE**

V2:

A2:

KW: **5**

HP

U./MIN: **1835**

APPLIC.: **Trazione**

SERV: **S2 - 50 MI**

CODICE: **KLMT1549-**

RA178018



ROTAZIONE V.L.A.: Entrambi i sensi

Ø 177

X 295

mors 4

CARR.: **STEINBOCK**

WR16

MOTORE: **STEINBOCK**

TIPO: **177 4MO BF C.160**

ARM. V1: **48**

A1: **130**

ECC.: **COMPOUND**

V2:

A2:

KW: **5**

HP

U./MIN: **2350**

APPLIC.: **Trazione**

SERV: